

CRUZE CHAINOIL

Premium quality AW hydraulic oil

Product Definition

It is black colored chain oil which has been formulated with superior synthetic oils and high performance additives. It is long-lasting and resistant to high temperatures.

Application/Usage

It is used for chain lubrication at high temperatures. It is applied by roll brush, pistol or dropper. Mixing with mineral oils may adversely impact the product performance.

Product Package

200 Lt - 20Lt - 4Lt - 1Lt.

Storage

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	UNIT	TEST VALUES	TEST METHOD
APPEARANCE		Black	---
Density 15°C		0.935	ASTM D-1298
Viscosity 40°C	mm ² /s	150	ASTM D-445
Flash Point	°C	250	ASTM D-92

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."