

CRUZE SUPER 20W50
HIGH PERFORMANCE ENGINE OIL

Product Definition

CRUZE SUPER is high performance, multi-grade motor oil for gasoline and diesel motors during four seasons, produced by blending the high quality mineral oils with the exclusive additives.

Application/Usage

CRUZE SUPER has been formulated for use in gasoline engines of vehicles (trucks, buses, business and agricultural machines, etc..) and commercial vehicles. It is also suitable for use in gasoline and diesel engines of light/medium duty vehicles that are worked long-distance transport.

Advantages/Benefits

- Provides constant lubrication in any road and climate conditions. Can be used four seasons Especially in winter, allows easy operation of the engine and minimize wear.
- Prevents wear, oxidation, corrosion and foam formation, provides excellent motor protection.
- Has a high viscosity index value and contains exclusive additives which protects the engine and prolongs its life.
- Reliable protection against deposits, sludge and varnish during extremely high thermal stress and stop-start driving Contains a detergent/dispersant additive which cleans up the engine.
- Rapid oil circulation after start-up; which reduces cold-start and warm-up wear.

- Provides long sump life and extends the oil changing periods.
- Increases the motor performance to the maximum level.
- Has low oil consumption thanks to the excellent viscosity control property.
- Has the ability to control of oil thickening caused by soot formation.

Specifications/Approvals

API SG/CD

Product Package

200 Lt - 20Lt – 4Lt.

Storage

Protect from direct sunlight and rain. Store in the original closed drums and in covered areas. Storage temperature must be between (+5)-(+40)°C.

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application. Used or waste product should not be allowed to contaminate soil or water. Used or waste product should be disposed of in accordance with local regulations. For further guidance on product Health and Safety refer to the appropriate Material Safety Data Sheet.

TECHNICAL PROPERTIES	UNIT	TEST VALUES	TEST METHOD
SAE Grade		20W -50	DIN 51 511
Density 15°C		0.885	ASTM D-1298
Viscosity 40°C	mm ² /s	166.0	ASTM D-445
Viscosity 100°C	mm ² /s	19.50	ASTM D-445
Viscosity Index		100	ASTM D-2270
Flash Point	°C	240	ASTM D-92
Pour Point	°C	-21	ASTM D-97
Base Number	mgKOH/g	8	ASTM D-2896B

"The above information is derived from our quality checks. Given values are typical of current production. While future production will conform to our specification, variations in these characteristics may occur. Quality Control Analysis Report for to learn properties of the product that is supplied can give. It does not relieve the purchaser from examining product upon delivery and gives no assurance of the product for any particular purpose. Due to continual product research and development, the information contained herein is subject to change without notification."